

Caratteristiche dei carburatori	VEICOLI							
	50 Mod. VSA 1 VSA2 - VSA3	90 - 90 SS. 125 Mod. V9A 1 V9SS - VMA1	125 Mod. VMA2 - VMB1	125 - 150 Mod. VNC1 VNL 2 - VNL 3 VLB 1	150 Mod. VBC 1	180 Mod. VSC 1	180 Mod. VSD 1	200 Mod. VSE 1
Tipo dell'Orto (ved. fig. 32).	SHB 16/10	SHB 16/16	SHB 19/19	SI 20/20 D	SI 20/15 D	SI 27/23	SI 20/20 D	SI 24/24 E
Getto max	51/100	74/100	74/100 (VNA2) 76/100 (VMB1)	102/100	88/100	120/100	109/100	118/100
Getto minimo	38/100	45/100	45/100 (VNA2) 42/100 (VMB1)	50/100	42/100	50/100	50/100	50/100
Calibratore dell'emulsionatore	—	—	—	160/100	120/100	160/100	160/100	160/100
Calibratore aria Coperchio getti	—	—	—	160/100	160/100	—	—	120/100
Emulsionatore (sigla)	—	—	—	BE 3	E 1	BE 2	BE 2	BE 3
Getto starter	50/100	50/100	60/100	60/100	60/100	60/100	60/100	60/100